HYBRIDFLUSH® AUTOMATIC

ADA Floor Mount High Efficiency Flush Valve System

Model AEF1012AT12

Description

Battery Powered, Sensor Operated HYBRIDFLUSH® Top Mount Complete HET System with Exposed Automatic Water Closet Flushometer and ADA Vitreous China Fixture.

Flush Cycle

☐ Model AEF1012AT12 (1.28 gpf/4.8 Lpf)

Specifications

Flushometer Specification (Model AEF-801-CT-12)

- Patented BRV® and Gear Motor Drive
- Hands Free Infrared Sensor Activation
- Vandal and Water Resistant Design
- Chrome Plated All Metal Housing
- Quiet Operation
- True Mechanical Override (Side)
  *Mechanical Button/Handle Works When Batteries are Drained
- Operates on (4) "AA" Alkaline Batteries (Included)
- Battery Life - 3+ Years
- "Low Battery" Blinking LED Indicator
- Easy Battery Replacement-No Water Shut Off Necessary
- Adjustable Sensor Angle
- Adjustable Sensor Distance
- Optional Three (3) Second Flush Delay Mode
- Optional 24-Hour Flush Mode
- Uses Proprietary Silicone Diaphragm with Filtered Bypass
- 1" I.P.S. Angle Stop
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker with Single Piece Hex Coupling Nut
- Spud Coupling and Flange for 1 ½" Top Spud
- Sweat Solder Kit and Wall Flange with Set Screw
- High Efficiency For Water Conservation

Compliance & Certifications

- ASSE 1037-2015
- ASME A112.1035-2015
- CSA B125.37-15

Listed By IAPMO

For Finish Variations Please Consult Factory

Accessories (Add suffix to model number for accessories)

☐ HC801 - Cover for Mechanical Flush Button

Fixture Specification (Model AUT-1012A)

- Complies with ADA Accessible Standards
- White Color
- Vitreous China
- Floor Mount Water Closet Bowl
- Elongated Rim
- 10" (254mm) Rough-In
- 1-1/2" (38mm) I.P.S. Top Spud Inlet
- 2" (50mm) Fully Glazed Trapway
- 11-1/2" (292mm) x 13" (330mm) Water Surface Area
- Direct Feed Jet
- 100% Factory Tested
- Toilet Seat Not Included

Compliance & Certifications

- ASME A112.19.2/CSA B45.1
- Energy Act of 1992
- ADA- With installation consideration for section 604 Water Closets, Accessibility Guidelines.
- ICC/ANSI A117.1
- TAS - With installation consideration for section: 4.16.3. Adult seat height 17" (432mm) to 19" (483mm).
- CSA B651 - With installation consideration for Clause 4.3.6 of the standard.
- ICC-ES PMG® Certified
- WaterSense® Listed

Plumbing System Requirements

- Minimum Flowing Pressure: 25 PSI
- Maximum Static Pressure: 80 PSI
- Minimum Flow Rate: 25 GPM

The HYBRIDFLUSH® Advantage

The **HYBRIDFLUSH®** is a revolutionary full-featured automatic/manual flush valve system. The **HYBRIDFLUSH®** incorporates a unique patented mechanism that allows for automatic/manual operation for unsurpassed reliability. The patented **HYBRIDFLUSH®** design allows for the original flush handle or push button to be used as an alternate flush option that is independent of the battery power. The **HYBRIDFLUSH®** by Advanced Modern Technologies Corporation is the most efficient, economical, and complete automatic flush valve system on the market.

WaterSense Meets EPA Criteria Certified by ICC-ES

HET HIGH EFFICIENCY TOILET

Warranty
5 Years

AXIO® TOUCH-FREE TECHNOLOGY

ADA Compliant

Architect/Engineer Approval

Job Name _____
Date _____
Model Specified _____
Quantity _____
Variations Specified _____
Customer/Wholesaler _____
Contractor _____
Architect _____

The information contained in this document is subject to change without notice.
Revision (10/17)

HYBRIDFLUSH® AUTOMATIC

ADA Floor Mount High Efficiency Flush Valve System

Model AEF1012AT12

Specifications

Operation:	**Hybrid (Automatic/Manual)**
Outer Casing:	**Standard-Chrome Metal**
Operating Water Pressure:	**15 PSI - 100 PSI**
Sensor Type:	**Infrared**
Battery Type:	**Four AA Alkaline Batteries**
Battery Life:	**3+ Years**
Arming Delay:	**5 Seconds**
Flush Delay:	**3 Seconds**
Sensing Range:	**18" (45cm) - 30" (75cm) Adjustable**
Ghost Flush:	**Once every 24 Hours From Last Flush**
Sensor Angle:	**Adjustable Angle**
Flush Cycle:	**Specified by Model**
Model AEF1012AT12	**1.28 gpf/4.8 Lpf**
Flush Mode:	**After Every Use**
Manual Override:	**Mechanical Flush Button or None**

Dimensions



Application



HYBRIDFLUSH® shown on water closet (toilet) with manual flush handle.



HYBRIDFLUSH® shown on water closet (toilet) with manual flush button.



Elongated Rim Nominal Dimensions:
28-5/16" (719mm) Long
15-7/16" (392mm) Wide
17-1/8" (435mm) High

Note: This toilet is designed to rough-in at the standard dimension of 10" (254mm) and 12" (305mm) from the wall to the C/L of the outlet.

This drawing reflects a 10" (254mm) rough-in and additional calculations must be considered for a 12" (305mm) or any other dimensional rough-in.

Disclaimer

Note: All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

Advanced Modern Technologies Corporation • 19800 Nordhoff Place • Chatsworth, CA 91311

Tel: (818) 883-2682 • Toll Free: (800) 874-7822 • Fax: (818) 883-2620 • www.amtcorporation.com

Copyright © 2017 AMTC