

WATER CLOSET FLUSHOMETER

Model MF-700-T11

Description

Exposed Water Closet Flushometer for Floor Mounted or Wall Hung Top Spud Bowls.

Flush Cycle

☐ Model MF-700-T11 (1.1 gpf/4.2 Lpf)

Specifications

Chrome Plated, Exposed, Diaphragm Type Water Closet Flushometer for use with Right or Left Side Water Supply


Features

- Quiet Operation
- Uses Proprietary Silicone Diaphragm with Filtered Bypass
- ADA Compliant Non-Hold Open Sealed Brass Handle
- 1" I.P.S. Angle Stop
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker with Single Piece Hex Coupling Nut
- Spud Coupling and Flange for 1 1/2" Top Spud
- Sweat Solder Kit and Wall Flange with Set Screw
- No External Water Volume Adjustment
- High Efficiency For Water Conservation

Code Compliance (Listed By ICC-ES)

- ASSE 1037-2015
- ASME A112.1035-2015
- CSA B125.37-15
- EPA WaterSense (When Used With a WaterSense Listed Bowl)

For Finish Variations Please Consult Factory





Warranty 5 Years



ADA Compliant

Architect	/Engineer	Approval
-----------	-----------	-----------------

Job Name	
Date	
Model Specified	
Quantity	
Variations Specified	
Customer/Wholesaler	
Contractor	
Architect	

The information contained in this document is subject to change without notice.

Advanced Modern Technologies Corporation • 8367 Canoga Avenue • Canoga Park, CA 91304 Tel: (818) 883-2682 • Toll Free: (800) 874-7822 • Fax: (818) 883-2620 • www.amtcorporation.com

Copyright © 2025 AMTC MF-700-T11 Revision (04/25)